

QC STL PRO-5.5X Specifications

Air Flow	Hi: 5,044 CFM / Med: 4,238 CFM / Low: 2,870 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,750 CFM / Med: 3,070 CFM / Low: 2,010 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,681 SQFT to 2,522 SQFT	
Energy Use	Hi: 490 Watts / Med: 268 Watts / Low: 88 Watts	
Amps	Hi: 6.31 / Med: 3.67 / Low: 1.30	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	3	
dBA	Hi: 50.7 / Med: 43.6 / Low: 35.6	
Minimum Attic Clearance	38"	
Duct Diameter	20"	
Duct Length	9 feet	
Motor Head Diameter	20 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	6.73 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	39" x 24" x 39"	
In The Box	-QC STL PRO-5.5X Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC STL PRO-5.5X
QuietCool Stealth Pro Line